


Türumbandung mit Umbandungsset optional möglich
 Charnières avec set de déplacement disponibles en option
 Optional re-hinging kit to change door hinge side
 Montaggio opposto delle cerniere possibile con il set disponibile separatamente



| | Deutsch | Français | Italiano | English |
|----|---|---|---|---|
| ① | Wasserausgang (Ø21mm) Max. Förderhöhe Pumpe: 1m Förderleistung 22l/min | Evacuation de l'eau (Ø21mm) Hauteur max. de refoulement pompe: 1m Capacité de débit 22l/min | Evacuazione dell'acqua (Ø21mm) Altezza mass. di convogliamento pompa: 1m Potenza di mandata 22l/min | Water outlet (Ø21mm) max. delivery head pump: 1m max. flow rate: 22l/min |
| ①a | Wasserausgang (nur bei Ablaufventil) | Evacuation de l'eau (seulement pour vanne d'écoulement) | Evacuazione dell'acqua (solo per valv. di scarico) | Water outlet (Appliances with an outlet valve only) |
| ② | Kalt- / Weich- / Regen- wasseranschluss (3/4") | Eau de pluie froid / douce (3/4") | Acqua piovana fredda / decalcificata (3/4") | cold / soft / rain water connection (3/4") |
| ③ | Kalt- oder Warm- wasseranschluss (3/4") | Raccordement eau froide ou chaude (3/4") | Alimentazione d'acqua fredda o calda (3/4") | Cold or hot water connection (3/4") |
| ④ | Elektroanschluss | Raccordement électrique | Collegamento elettrico | Electrical connection |

Massblatt Waschautomat Breite 630
 Plan d'installation machine a laver largeur 630
 Piano d'installazione lavatrice larghezza 630
 Dimension sheet washing machine width 630

| | | |
|------|------------|-----|
| Gez. | 05.04.2016 | rsc |
| Frg. | 12.05.2017 | rsc |
| Geä. | 12.05.2017 | rsc |

Masstab: 1:25

538772AC